



## LED diody – výkonové

Výkonové (I<sub>F</sub> při T<sub>A</sub>=25°C)

typ	barva světla	typ čočky	λ [nm]	U <sub>F</sub> [V]	I <sub>F</sub> [mA]	S <sub>v</sub> [lm]	2θ <sup>1/2</sup> [°]
LED8*R 0W5 HPB8-45KR	červená	transparentní	625-630	2.10	350	20	100
LED8*Y 0W5 HPB8-44KY	žlutá	transparentní	590-595	2.10	350	30	100
LED8*G 0W5 HPB8-43KG	zelená	transparentní	520-525	3.60	350	30	100
LED8*G 3W HPB8b-43K3G	zelená	transparentní	520-525	3.50	700	55	120
LED8*B 0W5 HPB8-48KB	modrá	transparentní	470	3.60	350	25	100
LED8*B 3W HPB8b-48K3B	modrá	transparentní	470	3.50	700	30	120
LED8*W 0W5 HPB8-49KW	bílá	transparentní	0.30-0.31	3.60	350	35	100
LED8*W 3W HPB8b-49K3W	bílá	transparentní	0.30-0.31	3.60	700	35	120

Výkonové (I<sub>F</sub> při T<sub>A</sub>=25°C)

typ	barva světla	typ čočky	λ [nm]	U <sub>F</sub> [V]	I <sub>F</sub> [mA]	S <sub>v</sub> [lm]	2θ <sup>1/2</sup> [°]
LED8*R 0W5 HPB8-45KR/PCB	červená	transparentní	625-630	2.10	350	20	100
LED8*Y 0W5 HPB8-44KY/PCB	žlutá	transparentní	590-595	2.10	350	30	100
LED8*G 0W5 HPB8-43KG/PCB	zelená	transparentní	520-525	3.60	350	30	100
LED8*G 3W HPB8b-43K3G/PCB	zelená	transparentní	520-525	3.50	700	55	120
LED8*B 0W5 HPB8-48KB/PCB	modrá	transparentní	470	3.60	350	25	100
LED8*B 3W HPB8b-48K3B/PCB	modrá	transparentní	470	3.50	700	30	120
LED8*W 0W5 HPB8-49KW/PCB	bílá	transparentní	0.30-0.31	3.60	350	35	100
LED8*W 3W HPB8b-49K3W/PCB	bílá	transparentní	0.30-0.31	3.60	700	60	120

