


# SKM450GB33F



SEMITRANS® 20

## SKM450GB33F

### Features


- 3.3 kV F-IGBT
- 450A half bridge
- Low  $V_{ce}$ ,  $E_{off}$  and  $R_{th}$
- High power density
- Low inductance module design
- T-sensor
- Easy paralleling and easy power scaling
- For flexible and compact medium voltage inverters

### Absolute Maximum Ratings


Symbol	Conditions	Values	Unit	
<b>IGBT</b>				
$V_{CES}$	$T_j = 25\text{ °C}$	3300	V	
$I_C$	$T_j = 150\text{ °C}$	$T_c = 25\text{ °C}$	760	A
		$T_c = 80\text{ °C}$	542	A
$I_{Cnom}$		450	A	
$I_{CRM}$	$I_{CRM} = 2 \times I_{Cnom}$	900	A	
$V_{GES}$		-20 ... 20	V	
$t_{psc}$	$V_{CC} = 2200\text{ V}$ , $L_s = 40\text{ nH}$ , $R_{Gon} = 6.8\text{ }\Omega$ , $R_{Goff} = 68\text{ }\Omega$ , $V_{GE} \pm 15$ , $T_j = 150\text{ °C}$ , $V_{CES} \leq 3300$	10	$\mu\text{s}$	
$T_j$	Operation	-50 ... 150	$^{\circ}\text{C}$	
<b>Inverse diode</b>				
$I_F$	$T_j = 150\text{ °C}$	$T_c = 25\text{ °C}$	674	A
		$T_c = 80\text{ °C}$	476	A
$I_{Fnom}$		450	A	
$I_{FRM}$	$I_{FRM} = 2 \times I_{Fnom}$	900	A	
$I_{FSM}$	$t_p = 10\text{ ms}$ , $\sin 180^{\circ}$ ,	t.b.d.	A	
$T_j$	Operation	-50 ... 150	$^{\circ}\text{C}$	
<b>Module</b>				
$I_{t(RMS)}$		1000	A	
$T_{stg}$		-55 ... 150	$^{\circ}\text{C}$	
$V_{isol}$	AC sinus 50 Hz, $t = 1\text{ min}$	6000	V	

### Characteristics

Symbol	Conditions	min.	typ.	max.	Unit	
<b>IGBT</b>						
$V_{CE(sat)}$	$I_C = 450\text{ A}$ $V_{GE} = 15\text{ V}$ chipelevel	$T_j = 25\text{ °C}$	1.75	2.07	2.37	V
		$T_j = 150\text{ °C}$	2.43	2.86	3.26	V
$V_{GE(th)}$	$V_{CE} = 10\text{ V}$ , $I_C = 450\text{ mA}$ , $T_j = 25\text{ °C}$	5.5	6.5	7.5	V	
$I_{CES}$	$V_{GE} = 0\text{ V}$ $V_{CE} = 3300\text{ V}$	$T_j = 25\text{ °C}$			0.3	mA
		$T_j = 150\text{ °C}$		15	50	mA
$C_{ies}$	$V_{GE} = 0\text{ V}$ , $V_{CE} = 10\text{ V}$ , $f = 0.1\text{ MHz}$ , $T_{vj} = 25\text{ °C}$		24.0		nF	
$Q_G$	$V_{GE} = -15\text{ V} \dots 15\text{ V}$		1296		nC	
$R_{Gint}$	$T_j = 25\text{ °C}$		6.2		$\Omega$	
$t_{d(on)}$	$V_{CC} = 1800\text{ V}$ $I_C = 450\text{ A}$	$T_j = 150\text{ °C}$		326	ns	
$t_r$	$V_{GE} = +15/-15\text{ V}$ $R_{Gon} = 6.8\text{ }\Omega$	$T_j = 150\text{ °C}$		118	ns	
$E_{on}$	$R_{Goff} = 12\text{ }\Omega$	$T_j = 150\text{ °C}$		601	mJ	
$t_{d(off)}$	$R_{Goff} = 12\text{ }\Omega$	$T_j = 150\text{ °C}$		1180	ns	
$t_f$	$di/dt_{on} = 3500\text{ A}/\mu\text{s}$ $di/dt_{off} = 3400\text{ A}/\mu\text{s}$	$T_j = 150\text{ °C}$		291	ns	
$E_{off}$	$du/dt = 1250\text{ V}/\mu\text{s}$ $L_s = 35\text{ nH}$	$T_j = 150\text{ °C}$		601	mJ	
$R_{th(j-c)}$	per IGBT			0.035	K/W	



GB




**SEMITRANS® 20**

## SKM450GB33F

### Features

- 3.3 kV F-IGBT
- 450A half bridge
- Low  $V_{ce}$ ,  $E_{off}$  and  $R_{th}$
- High power density
- Low inductance module design
- T-sensor
- Easy paralleling and easy power scaling
- For flexible and compact medium voltage inverters

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
<b>Inverse diode</b>						
$V_F$	$I_F = 450\text{ A}$		1.75	2.05	2.34	V
	$V_{GE} = 0\text{ V}$ chipllevel	$T_j = 150\text{ °C}$	1.93	2.25	2.57	V
$I_{RRM}$	$I_F = 450\text{ A}$	$T_j = 150\text{ °C}$		493		A
$Q_{rr}$	$di/dt_{off} = 3600\text{ A}/\mu\text{s}$	$T_j = 150\text{ °C}$		442		$\mu\text{C}$
$E_{rr}$	$V_{GE} = \pm 15\text{ V}$ $V_{CC} = 1800\text{ V}$	$T_j = 150\text{ °C}$		542		mJ
$t_{rr}$	$L_s = 35\text{ nH}$	$T_j = 150\text{ °C}$		1.49		$\mu\text{s}$
$R_{th(j-c)}$	per diode				0.055	K/W
<b>Module</b>						
$L_{CE}$	Between $C_1(\text{main})$ and $E_2(\text{main})$			9		nH
$R_{CC'+EE'}$	measured per switch, $R_{CAUXC'}$ + $R_{EAUXE'}$	$T_C = 25\text{ °C}$		t.b.d.		$\text{m}\Omega$
		$T_C = 125\text{ °C}$		0.44		$\text{m}\Omega$
$R_{th(c-s)}$	per switch			0.02		K/W
$M_s$	to heat sink M6			5.5	6	Nm
$M_t$		to terminals M3		0.6	0.8	Nm
		to terminals M8		14.4	15	Nm
<b>Temperature Sensor</b>						
$R_{25}$	$T_C = 25\text{ °C}$			$5 \pm 5\%$		$\text{k}\Omega$
$B_{25/50}$				3375		K



**GB**




Fig. 1: Typ. output characteristic, inclusive  $R_{CC+EE}$




Fig. 2: Rated current vs. temperature  $I_C = f(T_C)$




Fig. 3: Typ. turn-on /-off energy =  $f(I_C)$




Fig. 4: Typ. turn-on /-off energy =  $f(R_G)$




Fig. 6: Typ. gate charge characteristic




Fig. 7: Typ. switching times =  $f(I_C)$




Fig. 8: Typ. switching times = f ( $R_G$ )




Fig. 9: Transient thermal impedance




Fig. 10: Typ. diode forward charact., incl.  $R_{CC+EE'}$




Fig. 11: Typ. diode peak reverse recovery current






Fig. 12: Typ. diode peak reverse recovery charge



SEMITRANS 20



GB

This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, chapter IX.

## **\*IMPORTANT INFORMATION AND WARNINGS**

The specifications of SEMIKRON products may not be considered as guarantee or assurance of product characteristics ("Beschaffenheitsgarantie"). The specifications of SEMIKRON products describe only the usual characteristics of products to be expected in typical applications, which may still vary depending on the specific application. Therefore, products must be tested for the respective application in advance. Application adjustments may be necessary. The user of SEMIKRON products is responsible for the safety of their applications embedding SEMIKRON products and must take adequate safety measures to prevent the applications from causing a physical injury, fire or other problem if any of SEMIKRON products become faulty. The user is responsible to make sure that the application design is compliant with all applicable laws, regulations, norms and standards. Except as otherwise explicitly approved by SEMIKRON in a written document signed by authorized representatives of SEMIKRON, SEMIKRON products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury. No representation or warranty is given and no liability is assumed with respect to the accuracy, completeness and/or use of any information herein, including without limitation, warranties of non-infringement of intellectual property rights of any third party. SEMIKRON does not assume any liability arising out of the applications or use of any product; neither does it convey any license under its patent rights, copyrights, trade secrets or other intellectual property rights, nor the rights of others. SEMIKRON makes no representation or warranty of non-infringement or alleged non-infringement of intellectual property rights of any third party which may arise from applications. Due to technical requirements our products may contain dangerous substances. For information on the types in question please contact the nearest SEMIKRON sales office. This document supersedes and replaces all information previously supplied and may be superseded by updates. SEMIKRON reserves the right to make changes.